

Quikstak™ SP15 Series

Heavy-duty self-drive pallet stackers with 1.5-tonne capacity

The Quikstak SP15 Series is a range of heavy-duty self-drive pallet stackers, with a capacity of 1500kg and lift heights from 1.6 metres to as high as 5.6 metres. Optionally equipped with 'magic-eye' automatic height adjustment, the SP15 is suitable for warehousing, despatch, manufacturing, stacking and general materials handling operations, in any industry.

The SP15 is powered by a new self-drive unit, with a brushless electric motor and intelligent regenerative braking system. Combined with a bank of lead-acid batteries delivering 200Ah, this permits all-day use in even the most demanding of environments.

Both the straddle legs and forged forks on the SP15 are width-adjustable, allowing the stacker to lift all common types of pallet, as well as traverse warehouse aisles as narrow as 1200mm. The tiller includes infinitely-variable drive controls, ergonomic raise/lower buttons and a safety sounder, all accessible with both hands.

Like all Quikstak S-Series products, the SP15 complies with a range of international quality and safety standards, and is manufactured in an ISO 9000 certified plant. It is the only heavy-duty, high-reach pallet stacker available which has been specifically optimised for Australasian conditions.



The way the Quikstak magic-eye works



Unloading timber onto conveyor using auto infra-red eye sensor

As load decreases the height automatically raises to the conveyor height

These are our standard model basic specifications listed below. Please refer to our website for full detailed specifications on each model and video of these in operation.

The standard model lift height is 1.6 metres however other custom lift heights are available up to 3 metres with the S10 and SP10 models and up to 5.6 metres with the SP15 model. Please contact us for a quotation on your particular requirements.

Model	Description	Lift Capacity	Travel Speed	Overall Size (WxLxH)	Lift Height	Fork Length
S10	Quikstak	1000kg	Operator Dependent	1532x1735x2145mm	1600mm	1070mm
SP10	Quikstak	1000kg	6.0km/h	1532x1500x2145mm	1600mm	1150mm
SP15	Quikstak	1500kg	6.0km/h	1582x2095x1895mm	1600mm	1150mm